BOARDS 25mm x 150mm (1" x 6")
OR 25mm x 200mm (1" x 8")

RAIL 50mm x 150mm (2" x 6")

FASCIA 25mm x 150mm (1" x 6")

POST 150mm x 150mm (6" x 6")

DECORATIVE WOOD TRIM
25mm x 75mm (1" x 3")

170mm (6.5")

63mm (2.5")

VARIES TO 1825mm (6'-0")

100mm (4")

±900mm (±36")

300mm (12")

150mm x 150mm (6" x 6") PRESSURE TREATED
POST C/W CHAMFERED TOPCUT, SAND SMOOTH

20mm (3/4") DEEP ROUTER CUT, 25mm (1")
WIDE OR DOUBLE BEVEL

1 - 50mm x 150mm (2"x 6") TOP RAIL FIXED
SECURELY TO POST WITH 89mm COATED NAILS

1 - 25mm x 150mm (1" x 6") FASCIA FIXED TO
RAILINGS WITH 75mm COATED NAILS

1 - 25mm x 75mm (1" x 3") DECORATIVE WOOD TRIM FIXED
TO FACIA WITH 50mm COATED NAILS

1 - 25mm x 150mm(1" x 6") OR 25mm x 200mm
(1" x 8") ROUGH BOARDS BUTTED TOGETHER &
NAILED TO STRINGERS WITH 50mm ARDOX NAILS

1 - 50mm x 100mm (2" x 4") SUPPORT RAIL, NAIL
TO POSTS

1 - 50mm x 150mm (2" x 6") BOTTOM RAIL, NAILED
TO POST LOCATIONS (AS PER TOP RAIL) WITH
89mm COATED NAILS

1 - 25mm x 150mm (1" x 6") BOTTOM FASCIA,
TOENAIL TO POSTS & BOARDS

CONCRETE BASE

150mm DEPTH GRAVEL BASE TO BE
DETERMINED / CONFIRMED BASED ON LOCAL
SITE CONDITIONS

COLOUR
NOTES: STAIN COLOUR
TO BE TIMBERLOX
SOLID HIDE STAINS
(CEDAR) AVAILABLE
FROM CLOVERDALE
PAINTS.

STAIN NOTES:
- FIRST COAT EVENLY APPLIED
PRIOR TO ASSEMBLY WITH ALL
CUT ENDS DIPPED.
- SECOND COAT EVENLY
APPLIED TO COVER ALL
EXPOSED SURFACES OF FENCE
IN PLACE.
- STAIN TO BE APPLIED AS PER
MANUFACTURER'S SPEC.

NOTES:
-ALL HARDWARE TO BE GALVANIZED
-FENCE TO BE LOCATED WHOLLY ON
PRIVATE PROPERTY, WITH 150mm
SETBACK FROM PUBLIC PROPERTY
LINES
-STRUCTURAL STRINGER IS (2"x6")
FOR TOP AND BOTTOM AND (2"x4")
FOR CENTER
-FASCIA IS (1"x6")
-DECORATIVE WOOD TRIM IS (1"x3")

WOOD SCREEN FENCE DETAIL

SCALE 1: 20